



syntha pulvin

SITE APPLIED REMEDIAL SYSTEMS (FOR SCRATCHES OR SMALL AREAS OF DAMAGE)

Wherever possible, SYNTHA PULVIN coated items that have been damaged should be reprocessed by a SYNTHA PULVIN Applicator i.e. stripped, pre-treated and re-coated.

However, if the SYNTHA PULVIN coating suffers on site damage and the coated item cannot be removed it should be repaired using a suitable colour matched remedial liquid paint system from Breakwells Paints, 1 Harden Road, Leamore, Walsall WS3 1EL (tel. 01922 400444, <http://www.breakwellspaints.co.uk/>) or any other reputable paint supply company.

The particular method of repair, and repair system to be adopted, will be dictated by the nature of the required repair. Comprehensive product data and method statements are available from Breakwells Paints. Other reputable paint supply companies should be in a position to supply similar information. The method statement will describe:-

1. Surface preparation
2. Practice to be adopted if bare substrate is showing
3. Practice to be adopted if impact damage has resulted in indentations that need to be filled.

It is important to recognise that liquid repair systems are unlikely to have durability equivalent to the original Syntha Pulvin coating and, accordingly, repaired areas may weather differently. No warranty is expressed or implied by Valspar Powder Coatings Ltd. relative to the use of repair and remedial paint systems and it remains the responsibility of the user / specifier to ensure that any repair system is suitable for the purpose intended.

Remedial systems are general-purpose air-drying paints for the repair of the factory applied SYNTHA PULVIN coating. They should be used only to repair small scratches or minor areas of damage. They are not designed to overcoat defective factory applied powder coatings. If there is any query concerning the quality of the SYNTHA PULVIN coating then the Approved Applicator who coated the work should be consulted immediately.

All remedial systems and the areas of metalwork coated in these materials are expressly excluded from the SYNTHA PULVIN guarantee. The SYNTHA PULVIN guarantee will continue to apply to any 'unrepaired' area of SYNTHA PULVIN coating, on any component, where the SYNTHA PULVIN coating has been unaffected by the repair.